

Nýty












Popis výrobku

Specializované nýty z vysoce kvalitního hliníku a oceli. Používají se k trvalému vzájemnému propojení prvků. Používají se v mnoha průmyslových odvětvích.

Charakteristika

- materiál: hliník-ocel;
- průměr: 3,2–4 mm;
- délka: 8–28 mm;
- průměr díry: 3,3–5 mm.

Technická data

			 mm	 mm	 mm	 mm		
HT2C160	5902801388873	50	3,2	8	3,3	2.5-4.5	50	200
HT2C161	5902801389276	50	3,2	10	3,3	4.5-6.5	50	200
HT2C162	5902801389290	50	4	8	4,2	2.5-4.5	50	200
HT2C163	5902801389481	50	4	10	4,2	4.5-6.5	40	160
HT2C164	5902801389740	50	4	13	4,2	7.5-9.5	40	160
HT2C165	5902801389771	50	4	16	4,2	10.5-12.5	40	160
HT2C166	5902801389832	50	4	18	4,2	10.5-12.5	30	120
HT2C167	5902801389849	50	4,8	8	5	2.5-4.5	30	120
HT2C168	5902801389856	50	4,8	10	5	4.5-6.5	30	120
HT2C169	5902801389863	50	4,8	13	5	7.5-9.5	20	80
HT2C170	5902801389870	50	4,8	15	5	9.5-11.5	20	80
HT2C171	5902801389887	50	4,8	18	5	12.5-14.5	20	80
HT2C172	5902801389900	50	4,8	24	5	18.5-20.5	20	80
HT2C173	5902801389917	50	4,8	28	5	23.5-25.5	20	80
HT2C174	5902801389931	800	4	10	4,2	4.5-6.5	20	80

